## In the Claims:

Please cancel claims 19-37 from prosecution. A complete listing of the claims proper claim identifiers is set forth below.

- (original) A mixed-gas insufflation system for mixing insufflation gases, comprising:
- a gas supply providing at least two sources of insufflation gas; and a mixer system including a chamber having at least two inlets and at least one outlet, wherein the at least two inlets of the chamber are in fluid communication with the gas supply, the mixer system for mixing the at least two sources of insufflation gas.
- 2. (original) The mixed-gas insufflation system of claim 1 wherein the mixer system further comprises a tubing system corresponding to each source of insufflation gas, the tubing system having a first end attached to the source of insufflation gas and a second end attached with an inlet of the at least two inlets of the chamber.
- 3. (original) The mixed-gas insufflation system of claim 2, further comprising activation means for selecting an insufflation gas to enter the corresponding tubing system.
- 4. (original) The mixed-gas insufflation system of claim 2, wherein the tubing system further comprises a flow valve to allow the flow of insufflation gas and a metering valve to control the flow of insufflation gas.
- 5. (original) The mixed-gas insufflation system of claim 1, wherein the chamber further comprises at least one baffle.
- 6. (original) The mixed-gas insufflation system of claim 5, wherein the chamber further comprises four baffles.

- 7. (original) The mixed-gas insufflation system of claim 1, wherein the chamber further comprises a plate having a plurality of holes.
- 8. (original) The mixed-gas insufflation system of claims 1, 5, 6 or 7, wherein the mixing chamber further comprises a fan.
- 9 (original) The mixed-gas insufflation system of claim 1, wherein the at least two sources of insufflation gas are different from each other.
- 10. (original) The mixed-gas insufflation system of claim 1, wherein the at least two sources of insufflation gas include oxygen.
- 11. (original) The mixed-gas insufflation system of claim 1, wherein the mixer system further comprises a sensor for identifying the presence of the insufflating gas associated with the corresponding tubing system.
- 12. (original) The mixed-gas insufflation system of claim 11, wherein the sensor further comprises a resistor block that senses the assigned ohmic value assigned to the insufflating gas.
- 13. (original) The mixed-gas insufflation system of claim 11, wherein the sensor further comprises a gas analyzer.
- 14. (original) The mixed-gas insufflation system of claim 1, wherein the mixer system further comprises at least one dual-capacity tube having an inlet for attachment to at least one outlet of an insufflator;
- .15. (original) The mixed-gas insufflation system of claim 1, further comprising a multi-output insufflator having:

  at least two inputs:

at least two delivery paths attached to the at least two inputs for allowing the flow of insufflation gases from at least two pressurized sources attached to the at least two delivery paths;

a central processing unit for monitoring and controlling the flow of insufflation gas passing through the at least two delivery paths;

at least two output lines attached to the at least two delivery paths; and wherein the mixer system is located internal to the multi-output insufflator and along the at least two delivery paths for mixing the insufflation gas.

- 16. (original) The mixed-gas insufflation system of claims 1 or 15 further comprising a multi-lumen catheter having at least one inlet attached with the at least one output of the chamber and at least one inlet for attachment with a source of liquid.
- 17. (original) The mixed-gas insufflation system of claims 1 or 15 further comprising a humidification system having at least one inlet attached with the at least one output of the mixing chamber.
- 18. (original) The mixed-gas insufflation system of claim 1, wherein the chamber further comprises at least one output in fluid communication with a connector for insertion into a surgical site and a catheter having at least one lumen and an outlet for insertion into the surgical site.

19-37. (cancelled)